MOMENTIVE

MATERIAL SAFETY DATA SHEET

Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer Name: Momentive Performance Materials LLC

260 Hudson River Road Waterford NY 12188

Revised: 08/22/2013

Prepared by Product Safety Team 1-800-424-9300 MSDS Contact 1-888-443-9466

Information 4information@momentive.com

Chemical Family/Use: Sealant

Formula: MixtureSilicone sealant

HMIS

Health: 2 Flammability: 1 Reactivity: 0

NFPA

Health: 2 Flammability: 1 Reactivity: 0

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Irritating to eyes, respiratory system and skin. Adverse liver and reproductive effects reported in animals. Attention: Not for injection into humans.

Form: Paste Color: Red Odor: Acetic acid.

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed.

SKIN

Causes mild skin irritation.

INHALATION

None known.

EYES

May cause eye irritation.

MEDICAL CONDITIONS AGGRAVATED

None known.



Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

SUBCHRONIC (TARGET ORGAN)

Liver injury.; Reproductive hazard.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal; Eye

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS-No.	WGT. %
A. HAZARDOUS		
Methyltriacetoxysilane	4253-34-3	1 - 5 %
B. NON-HAZARDOUS		
Siloxanes and Silicones, di-Me hydroxy terminated	70131-67-8	30 - 60 %
Dimethylpolysiloxane	70131-67-8	10 - 30 %
Treated Fumed Silica	68583-49-3	10 - 30 %
Siloxanes & Silicones, Dimethylpolymers w/Methylsilsesquioxanes	68554-67-6	10 - 30 %
Red iron oxide	1332-37-2	1 - 5 %

4. FIRST AID MEASURES

INGESTION

If swallowed, do NOT induce vomiting. Give a glass of water. Do not give victim anything to drink if he is unconscious. Get medical attention.

SKIN

Wash with soap and water.



Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT:> 93.3 °C; 200 °FMETHODEstimatedIGNITION TEMPERATURE:Not applicableFLAMMABLE LIMITS LEL:Not applicableFLAMMABLE LIMITS UEL:Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.



Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics.

Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the finger and hands. Keep out of reach of children. Keep container closed. May generate formaldehyde at temperatures greater than 150 C(300 F). See Section 8 of the MSDS for Personal Protective Equipment.

STORAGE

Keep container tightly closed in a cool, well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Provide adequate general and local exhaust ventilation.; Eye washes and showers for emergency use.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Butyl rubber gloves are recommended.

EYE AND FACE PROTECTION

Safety glasses with side shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS-No.	Source	Value

MOMENTIVE

MATERIAL SAFETY DATA SHEET

Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°C): Not applicable VAPOR PRESSURE (20 C) (MM HG): Not applicable VAPOR DENSITY (AIR=1): Not applicable **FREEZING POINT:** No data available.

PHYSICAL STATE: Paste ODOR: Acetic acid. Color: Red

EVAPORATION RATE (BUTYL ACETATE=1): < 1 **SPECIFIC GRAVITY:** ca. 1.06 **DENSITY:** 1.06 g/cm3 ACID / ALKALINITY (MEQ/G): Not applicable Not applicable **SOLUBILITY IN WATER (20 C):** Insoluble Toluene

SOLUBILITY IN ORGANIC SOLVENT (STATE

SOLVENT):

VOLATILE ORGANIC CONTENT: 2.4 %(m) VOC EXCL. H2O & EXEMPTS (G/L): 26 g/l

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION.

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Silicon dioxide.; Formaldehyde.; This product contains methylpolysiloxanes which will likely generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and has been classified by the National Toxicology Program as as a known human carcinogen. A MSDS for formaldehyde is available from Momentive. See Section 11 for additional information on formaldehyde.

INCOMPATIBLE MATERIALS

None known.



Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: No data available.

CARCINOGENICITY

The National Toxicology Program (NTP) classifies formaldehyde as "known to be a human carcinogen" with respect to nasopharyngeal cancer, sinonasal cancer and myeloid leukemia. The International Agency for Research on Cancer (IARC) classifies formaldehyde as "carcinogenic to humans". U.S. OSHA regulates formaldehyde as a potential human carcinogen. See the OSHA Formaldehyde Workplace Standard at 29 CFR 1920.1048 (the "OSHA Standard"). Safe handling and use instructions are provided in this MSDS and in the OSHA Standard. OSHA has identified 0.5 ppm, calculated as an eight-hour time-weighted average ("TWA") concentration, as the "Action Level". Please review and understand the guidance contained in this MSDS, and refer to the OSHA Standard for regulatory requirements that might be applicable to your operation and use. Many studies and other evaluations have been performed concerning formaldehyde's potential to cause cancer. To review some of these studies and for further information go to www.osha.gov; http://monographs.iarc.fr; http://ntp-server.niehs.nih.gov; http://epa.gov; http://www.nap.edu and other authoritative websites then search on formaldehyde.

ACUTE DERMAL

Remarks: No data available.

ACUTE INHALATION

Remarks: No data available.

SENSITIZATION

No data available.

SKIN IRRITATION.

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

No data available.

OTHER EFFECTS OF OVEREXPOSURE

This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin



Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive., Acetic acid released during curing.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Ecotoxicological data for this product is not available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information: This product is not regarded as dangerous goods according to the national

and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Australia Inventory of Chemical y (positive listing)

Substances (AICS)

Canada DSL Inventory y (positive listing) EU list of existing chemical y (positive listing)

substances

Japan Inventory of Existing & New y (positive listing)

Chemical Substances (ENCS)

China Inventory of Existing y (positive listing)

Chemical Substances

Korea Existing Chemicals y (positive listing)

Inventory (KECI)

Canada NDSL Inventory n (Negative listing)

MOMENTIVE

MATERIAL SAFETY DATA SHEET

Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)

Philippines Inventory of Chemicals y (positive listing)

and Chemical Substances

(PICCS)

TSCA list y (positive listing)
New Zealand Inventory of y (positive listing)

Chemicals

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

CERCLA

PRODUCT COMPOSITION Chemical CERCLA Reportable Quantity

SARA (311,312) HAZARD CLASS

Acute Health Hazard

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Canadian Regulatory Information

WHMIS CLASSIFICATION

D2A - Very Toxic Material Causing Other Toxic Effects D2B - Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown

NE = none established REC = recommended ND = none determined V = recommended by vendor

SKN = skin TS = trade secret R = recommended MST = mist

NT = not tested STEL = short term exposure limit

ppm = parts per million ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).



Version: 1.14 08/22/2013

RTV106 ACETOXY SEALANT (red)